

## **AREA SCAN UVSS**



Motwane's Area Scan UVSS technology guarantees low distortion and consistent images for vehicles & makes it possible for further Al algorithm.

### **Built for you:**

- Modular design
- Built rugged with stainless steel
- Real time imaging

#### **Features**

Used to check the underneath parts of various vehicles. It can quickly and accurately identify the threat / contraband / contraband of the underlying person.

- ✓ High resolution imaging, output 4096P color images.
- ✓ Real time imaging, scanned parts of chassis will show up on display in real time.
- ✓ Support vehicles with different height of chassis, no limitation for vehicle length.
- ✓ Embedded bi-directional triggers, support bi-directional scan.
- ✓ Bi-directional LPR function can capture and recognize both front and rear license plate.
- Designed to withstand harsh environments.
- Generate area scan low distortion image.
- ✓ Provides all kinds of ISP functions, such as Brightness adjust, Saturation, Color Balance etc.
- ✓ Support high vehicle speed, up to 100km/h.
- ✓ Modular design, by replacing with spare parts within 10 minutes.
- ✓ Ultra slim design, only needs to dig into ground for less than 5 cm for installation.

#### THE IDEAL SOLUTION FOR









#### **ACCESS CONTROL**

Our products offer simple and easy integration with various Access control systems.











Biometric

Facial Recognition

QR Code

RFID

Mobile App





# TECHNICAL DETAILS

# AREA SCAN UVSS

MODEL	MUVSS-A
AREA SCAN SPEED	Forward: 0 - 100 km/h, Backward: 0 - 25 km/h
HEIGHT LIMIT	50 - 2000 MM
WIDTH LIMIT	< 4500 MM
LENGTH LIMIT	No Limit
VIEW ANGLE	> 180°
RESOLUTION	> 10000 x 4096
CAPTURE RATE	> 99.9%
IMAGING TIME	Real Time
AUTO EXPOSURE	Support
PROTECTOR MATERIAL	304 stainless steel
LOAD BEARING	60 Tones (vehicle Weight)
ABOVE GROUND	3 Cm
DIMENSION	1200mm x 300mm x 75mm
WEIGHT	27 KG
WORKING TEMPERATURE	-40°C - 70°C
PROTECTION LEVEL	IP 68

#### **SERVER**

SERVER	CPU: 15, Memory: 4G, Hard disk: 128G
POWER CONSUMPTION	<25W
POWER SUPPLY	DC 12V
WORKING TEMPERATURE	-10°C - 50°C
DIMENSION	235mm x 165mm x 50mm
WEIGHT	4 KG



#### TECHNICAL DETAILS

### **AREA SCAN UVSS**

#### **CONTROL BOX**

**VEHICLE DETECTOR** 2 Channel

**DETECTOR SENSITIVITY** 4 Level

POE 8 Ports 10/100/1000m Rj45

**POE STANDARD** IEEE802.3af/at

**ETH** 1 port 10/100/1000m RJ45

**SCANNER CONNECTOR** 1 Set

2 Channel **EXTERNAL TRIGGER** 

AC 220V **POWER SUPPLY** 

**WORKING TEMPERATURE** -10°C - 50°C

**DIMENSION** 263mm x 150mm x 78mm

**WEIGHT** 2 KG

#### LICENSE PLATE RECOGNITION CAMERA

**SENSOR** 1/2.8 inch CMOS

**RESOLUTION** 1920 x 1080

**VIDEO CODEC** H264, H265

**IMAGE CODEC JPEG** 

**DE-NOISE** 3DNR

**DYNAMIC RANGE** 96db

FIXED APERTURE **APERTURE** 

**CAPTURE RATE** > 99.5%

**POWER CONSUMPTION** < 24W

**WORKING TEMPERATURE** -10°C - 50°C


**PROTECTION LEVEL** IP 65



### TECHNICAL DETAILS

# AREA SCAN UVSS

# **GA LAYOUT**



Disclaimer: In view of the Motwane's policy of continuous development and improvement, the dimensions and specifications may be changed without prior notice or obligation. Colours of the products shown in this catalogue may not match the actual colour of the product due to printing limitations.